HF9413



Chandelier

Thank you for your purchase.

Welcome to the Avenue Lighting Family. Please follow these instructions carefully as they contain important information about the safety, use and disposal of this product. Read and understand all instructions before proceeding with assembly and installation of this fixture.

Electrical Rating: 120V, 60 Hz

-This fixture MUST be installed by a licensed electrician.

- -Read & understand the entire installation sheet.
- -DO NOT substitute any parts, leave parts out, or use parts that are worn out or broken.
- -The fixture is intended for installation in accordance with the National Electric Code (NEC and all local code specification
- -Use only the supplied LED driver to power the fixture.
- -Please wear gloves during installation to avoid damage to the plating.
- -Must be installed in a fixed location and be checked yearly.
- -Do NOT operate fixture if any lights are not operating or operating improperly or fixture could be further damaged.

Preparation:

Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration. If any parts are missing or damaged, DO NOT attempt to assemble the product.

Tools Required (not included):

Phillips screwdriverElectrical TapeFlathead screwdriverLadderWire StrippersSafety Glasses + Gloves

This Package includes

(2) Junction Box Screws

(3) Wire Connectors

(4) Plastic Anchor + Wood Screw

Assembly Instructions

- 1. Please turn off the power before installing the lamp. (fig A)
- 2. Remove the mounting bracket from the top box,
- According to the height of the fixture, tighten the downrods and tighten the nut inside the canopy
- The driver output line is connected to the fixture's body (- connect -) and (+ connect +)
 Then place the mounting bracket on the junction box. Then tighten the junction box
- screw, Buckle up the safety rope.
 Connect the lamp powerr cord to the main power cord of the junction box. (white to white & black to black)
- 7. To utilize 0-10V dimming: use wire purple (dim +) & gray (dim-)
- Wrap the Naked copper in the junctio bx around the green screw. Lock the green screw in the tooth hole. Connect the Naked copper of the lamp and the naked copper of hte junction box with the terminal.
- Secure the canopy to the mounting plate using the mounting screws
 turn on the power (fig B)

NOTE:

- This device complies with art 15 of the FCC Rules. Operation is subject to the following two conditions: (1)this device may not cause hamful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation (3) Importer: Avenue Lighting, 9000 Fullbright Ave. Chatsworth, CA 91311 P:800.798.0409
- Please note that changes or modifications of this product is not expressly approved by the party responsible for compliance could void the user's authority too operate the equipment.
- 3. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection aainst harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructionsm may cause harmful interference to radio communications. However, there is no guarantee that interferencee will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
 - A. Reorient or relocate the receiving antenna
 - B. Increase the Separation between the equipment and receiver
 - C. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
 - D. Consult the deealer or an experiences radio/TV technician for help

www.AvenueLighting.com

